

DesignLights Consortium



Classification	Premium
Primary Use	Fuel Pump Canopy Luminaires
Reported Input Wattage	39.9 W
Reported Light Output	5170 lm
Reported CCT	5000 K
Reported CRI (Ra)	84
Product ID	S-X264PD
DLC Family Code	YYYYFFK
Listing Status	Listed
Date Qualified	2022-04-21

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-X264PD
Manufacturer	T-1 Lighting Inc.
Brand	T-1 Lighting
Model Number	T1-CPLED10/U/40-G-50
Parent	No
Classification	Premium
DLC Family Code	YYYYFFK
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Mid Output
Primary Use Designation	Fuel Pump Canopy Luminaires

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Exterior Photocell, Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Backlight (TM-15 BUG)	2
Reported Light Output	5170 lm
Reported Efficacy (AC)	129.54 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	84
Reported R9	16
Reported IES Rf	85
Reported IES Rg	97
Reported IES Rcs,h1	-11
Reported Default Light Output	5170 lm
Reported BUG Rating	B2 U3 G1

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	39.9 W
Reported Total Harmonic Distortion	16.3 %
Reported Power Factor	0.942
Reported Default Input Wattage	39.9
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2022-04-21	Listed	5.1	Premium
------------	--------	-----	---------