

# DesignLights Consortium



Classification	Premium
Primary Use	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	30 W
Reported Light Output	3840 lm
Reported CCT	3500 K
Reported CRI (Ra)	82
Product ID	S-LQ93S2
DLC Family Code	<a href="#">SLFASD</a>
Listing Status	Listed
Date Qualified	2023-08-29

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-LQ93S2
Manufacturer	T-1 Lighting Inc.
Brand	T-1 Lighting
Model Number	T1-CBLEDD22/MW30-MCCT
Parent	Yes
Classification	Premium
DLC Family Code	SLFASD
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces

## CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Multifunction Sensor, Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	3840 lm
Reported Efficacy (AC)	128 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	82
Reported R9	3
Reported IES Rf	80
Reported IES Rg	90
Reported IES Rcs,h1	-12
Reported Minimum Light Output	2700 lm
Reported Maximum Light Output	3900 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	3840 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	30 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	20 W
Reported Maximum Input Wattage	30
Reported Default Input Wattage	30 W
Voltage Range	120-277 V

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	3903 lm
Tested Efficacy (AC)	129.62 lm/W

Tested CCT	3383 K
Tested CRI (Ra)	82
Tested R9	3
Tested IES Rf	84
Tested IES Rg	94
Tested IES Rcs,h1	-13 %
Tested Duv	0.0023

## TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	30.1 W
Tested Total Harmonic Distortion	11.8 %
Tested Power Factor	0.969

## VERSION HISTORY VIEW DETAILS

2023-08-29	Listed	5.1	Premium
------------	--------	-----	---------