# **DesignLights Consortium**





Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	155 W
Reported Light Output	23250 lm
Reported CCT	4000 K
Reported CRI (Ra)	79
Product ID	S-7KEGLH
DLC Family Code	<u>EMWBDV</u>
Listing Status	Listed
Date Qualified	2023-08-04

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-7KEGLH
Manufacturer	T-1 Lighting Inc.
Brand	T-1 Lighting
Model Number	T1-L2HBLED/155-40
Parent	Yes
Classification	Premium
DLC Family Code	EMWBDV
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires		
General Application	High-Bay		
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings		

### **CONTROL FEATURES VIEW DETAILS**

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Daylight Sensing, Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	23250 lm
Reported Efficacy (AC)	150 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	79
Reported R9	-13
Reported IES Rf	81
Reported IES Rg	93
Reported IES Rcs,h1	-15
Reported Default Light Output	23250 lm

# REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	155 W
Reported Total Harmonic Distortion	7 %
Reported Power Factor	0.979
Reported Default Input Wattage	155 W
Voltage Range	120-277 V

### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Tested Light Output	22666 lm
Tested Efficacy (AC)	156.39 lm/W
Tested CCT	4048 K
Tested CRI (Ra)	79
Tested R9	-12
Tested IES Rf	81
Tested IES Rg	93
Tested IES Rcs,h1	-15 %

Tested Duv	0.0023	
------------	--------	--

## **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

Tested Voltage	120
Tested Input Wattage	144.9 W
Tested Total Harmonic Distortion	2.8 %
Tested Power Factor	0.997

### PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

SPDX File	Download File
-----------	---------------

### **VERSION HISTORY VIEW DETAILS**

2023-08-04	Listed	5.1	Premium